



## ELECTRONIC LEAK DETECTION

55100



### 55100 ELECTRONIC LEAK DETECTOR

**FEATURES:**

- 3 Levels Of Sensitivity (5 Levels Of Detection)
- Visual Leak Level Indicator
- Detects Leaks As Small As 3 gr (1/10 oz) Per Year
- Detects All Refrigerants, CFC'S, HCFC'S, HFC'S
- Includes a Custom Molded Carrying Case

### 55200 "INSPECTOR" 2 IN 1 ELECTRONIC / UV LEAK DETECTOR

**FEATURES**

- Ultra Bright UV/Blue LED Light
- UV Safety Glasses
- 6 Levels Of Sensitivity (15 Levels Of Detection)
- Tri-colored Visual Leak Level Indicator
- Mute Function
- Detects Leaks As Small As 3 gr (1/10 oz) Per Year
- Detects All Refrigerants, CFC'S, HCFC'S, HFC'S

55200



55500



### 55750 COMBUSTIBLE GAS LEAK DETECTOR

**SPECIFICATIONS:**

- Operating Temp: 0 to 52°C (32-125°F)
- Power Supply: 2 C-Size 1.5V Ni-MH Battery
- Battery Life: 8 hrs per cycle (1000 cycles)
- Warm-Up Time: 25 seconds
- Probe/Core Length: 381mm (15")
- Dimension: 178 x 178mm (7 x 7")
- Weight: .49 kg (1.10 lbs)
- Ultimate Sensitivity: 50 – 1000 ppm

**FEATURES:**

- Six Sensitivity Levels
- Reset Function
- Automatic Warm Up
- Bright LED Light
- Audible Leak Alarm & Visual Leak Size Indicator
- Rechargeable Ni-MH Battery
- Low Battery Indicator
- Custom Molded Carrying Case
- Made in USA

**DETECTS:**

Acetone, Acetylene, Ammonia, Benzene, Butane, Butanol, Chlorine, Ethane, Ethanol, Gasoline, Hexane, Hydrogen, Hydrogen Sulfide, Isobutane, Methane (natural gas), Methanol, Methyl Acetate, Methyl Chloride, Methyl Ether, Naptha, N-Butane, Pentane, Propane, Propanol, Sulfur Dioxide and Trichloroethane

### 55500 ELECTRONIC LEAK DETECTOR W/HEATED SENSOR

**SPECIFICATIONS:**

- Operating Temp: 0 to 52°C (32-125°F)
- Power Supply: 2 C-Size 1.5V Ni-MH Battery
- Battery Life: 8 hrs per cycle (1000 cycles)
- Warm-Up Time: 25 Seconds
- Dimension: 178 x 178mm (7 x 7")
- Weight: .49 kg (1.10 lbs)
- Ultimate Sensitivity: 3 gr (1/10 oz) per year

**FEATURES:**

- Six Sensitivity Levels
- Automatic Warm Up
- Reset Function
- Blue UV LED Light
- Detects all Refrigerants (CFC's, HCFC's, HFC's)
- Rechargeable Ni-MH Battery

- Low Battery Indicator
- High Volume Pump
- Dual-colored Visual LED Leak Size Display
- Meets and Exceeds SAE J1627
- Made in USA

55750

