



Mastercool[®] Inc.
"World Class Quality"

1 ASPEN DRIVE, RANDOLPH, NJ 07869
PHONE: 973-252-9119 / FAX: 973-252-2455
WEB: WWW.MASTERCOOL.COM

55975 *IntellaSense III*
COMBUSTIBLE GAS LEAK DETECTOR



SPECIFICATIONS

- Sensing Element: Heated Tin Oxide
- Sensor Life: 2000 hours
- Refrigerants: Detects combustible gases (see below)
- Response Time: less than 1 second
- Battery: 2 "C" Alkaline 6000 mAh batteries
- Operating Temperature Range: 0°F to 120°F
- Ultimate Sensitivity: 50 – 1000 ppm
- Probe:
 - Intelligent tip, with environment sensing element to eliminate the potential of false alarms.
 - Flexible 15.5 inch probe length for difficult to reach locations.
- Display:
 - Six vertical LED display with enabled selectively (red, yellow or green) to display information to the user such as:
 - The relative signal level of the detected leak
 - The selected sensitivity range (low/medium or high) of the unit
 - Diagnostic information: low battery, interference/wait, contaminated atmosphere readiness of the unit or fault conditions of the unit
- Keypad Controls:
 - ON/OFF button (push-on/push-off)
 - Volume/Mute button (high, low or mute)
 - Sensitivity button for High, Medium and Low sensitivity level selection
 - Peak button when multiple leaks are suspected (push enable/disable)

IntellaSense III
COMBUSTIBLE GAS LEAK DETECTOR

At the heart of this leak detector is a new low power metal oxide gas sensor with superior performance properties such as lower current consumption and sensor longevity. The new sensor is characterized by high sensitivity and fast response upon detecting the presence of extremely small levels of chlorofluorocarbon gases. For this reason, this sensor was selected and integrated into the 55975 Combustible Gas Leak Detector.

In addition, a powerful microprocessor was integrated into the design that automatically selects the best operating condition for the sensor to ensure optimum performance throughout its life.

55975 Intella Sense III Combustible Gas Leak Detector in a blow molded case with 2 "C" batteries, leak test vial and replacement filters

DETECTS:

Acetone, Acetylene, Ammonia, Benzene, Butane, Butanol, Chlorine, Ethane, Ethanol, Gasoline, Hexane, Hydrogen, Hydrogen Sulfide, Isobutane, Methane (natural gas), Methanol, Methyl Acetate, Methyl Chloride, Methyl Ether, Naptha, N-Butane, Pentane, Propane, Propanol, Sulfer Dioxide and Trichloroethane