

Printing date 06/18/2019 Reviewed on 06/18/2019

1 Company and Substance / Formulation Identification

- · Product identifier
 - · Product name: 53609 Engine Coolant
 - · Product Code 53609
 - Application of the substance / preparation Dyestuff/Colouring agent
- Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

Mastercool Inc. 1 Aspen Drive Randolph, NJ 07869 USA (973) 252-9119

Department: RegulatoryEmergency Telephone:

For Chemical / Medical Emergency, 24 hours: INFOTRAC: (800) 535-5053 (US and CDN) 1-352-323-3500 (INTL)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aguatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Additional information:

As per GHS rules, liquid hydrocarbons which display a low kinematic viscosity are categorized as aspiration hazards.

- Label elements
 - GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms GHS08
- Signal word Danger
- Hazard-determining components of labeling:

Distillates (petroleum), hydrotreated light naphthenic

Solvent naphtha (petroleum), heavy arom.

Hazard statements

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 2)

Printing date 06/18/2019 Reviewed on 06/18/2019

Product name: 53609: Engine Coolant

· Hazardou	s components:	
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic	50-100%
	♦ Asp. Tox. 1, H304	
64742-94-5	Solvent naphtha (petroleum), heavy arom.	<5%
	♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411	

4 First-aid measures

- · Description of first aid measures
 - · After inhalation: Supply fresh air; consult doctor in case of complaints.
 - After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
 - · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
 - · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
 - · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 3)

Printing date 06/18/2019 Reviewed on 06/18/2019

Product name: 53609: Engine Coolant

(Contd. from page 2)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
 - · Precautions for safe handling Prevent formation of aerosols.
 - · Protection against explosions and fires: No special measures required.
 - · Special Sensitivity: Keep container closed when not in use.
- · Conditions for safe storage, including any incompatibilities
 - Storage:
 - · Requirements for storerooms and containers:

Store only in the original receptacle.

No special requirements.

Further information about storage conditions: None.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Technical systems:

Facilities using this material should be equipped with an eye wash station and a safety shower.

- · Control parameters
 - · Components with limit values that require monitoring at the workplace:

64742-53-6 Distillates (petroleum), hydrotreated light naphthenic

ACGIH-TLV Short-term value: 10 mg/m³ Long-term value: 5 mg/m³

64742-94-5 Solvent naphtha (petroleum), heavy arom.

ACGIH-TLV Short-term value: 10 mg/m³ Long-term value: 5 mg/m³

- Additional Occupational Exposure Limit Values for possible hazards during processing:
 - Oil mists: When mists / aerosols can occur, the following are recommended: 5 mg/m3 ACGIH TLV
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
 - · Personal protective equipment:
 - General protective and hygienic measures:

Do not allow product to reach soil or surface water. Handle with care to minimize any exposure. The usual precautionary measures should be used when handling commercial/industrial chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Breathing equipment:

Use suitable respiratory protection in the event of exceeding established exposure limits.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:

Use of gloves suggested; concentrated dye/pigment products may stain skin if directly contacted.

Glove Material

chemical resistant gloves

No specified glove material; most liquid-impervious protective gloves will suffice.

• Eye protection: Goggles recommended during refilling.

(Contd. on page 4)

Printing date 06/18/2019 Reviewed on 06/18/2019

Product name: 53609: Engine Coolant

· Body protection: Protective work clothing

(Contd. from page 3)

9 Physical and chemical properties

 Information on basic physical and chemical properties

General Information

· Appearance:

· Form: Liquid · Color: Dark yellow Petrol-like · Odor: Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. · Boiling point/Boiling range: >260 °C (>500 °F)

· Flash point: >94 °C (>201.2 °F)

· Flammability (solid, gaseous): Not applicable.

· Decomposition temperature: · Auto igniting: Product is not selfigniting.

Product does not present an explosion hazard. Danger of explosion:

Not determined.

Density at 20 °C (68 °F): 0.9-0.95 g/cm3 (7.51-7.93 lbs/gal)

· Relative density Not determined. · Vapor density Not determined. · Evaporation rate Not determined.

· Solubility in / Miscibility with

· Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

· Dynamic: Not determined. Kinematic: Not determined.

Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
 - Chemical stability
 - · Thermal decomposition / conditions to be avoided: To avoid thermal decomposition do not overheat.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · **Incompatible materials**: No further relevant information available.
- · Hazardous decomposition products:

In the case of a fire, oxides of carbon, fumes, and smoke may be produced.

Printing date 06/18/2019 Reviewed on 06/18/2019

Product name: 53609: Engine Coolant

(Contd. from page 4)

11 Toxicological information

- Information on toxicological effects
 - Acute toxicity:
 - LD/LC50 values that are relevant for classification:

Known component toxicological information:

Product has not been tested.

64742-94-5 Solvent naphtha (petroleum), heavy arom.

Oral LD50 >5,000 mg/kg (rat)

- Primary irritant effect:
 - on the skin: Contact may cause irritation.
- on the eye: Contact may cause irritation.
- Sensitization: No sensitizing effects known.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- Carcinogenic categories
 - · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
- · **Mobility in soil** No further relevant information available.
- Additional ecological information:
 - · General notes:

Do not allow product to reach ground water, water course or sewage system.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

- · Uncleaned packagings:
 - · Recommendation: Packaging can be reused or recycled after cleaning.

HS

Printing date 06/18/2019 Reviewed on 06/18/2019

Product name: 53609: Engine Coolant

(Contd. from page 5)

14 Transport information

- · UN-Number
 - · DOT, ADR, ADN, IMDG, IATA Void
- · UN proper shipping name
 - · DOT, ADR, ADN, IMDG, IATA Void
- · Transport hazard class(es)
 - · DOT, ADR, ADN, IMDG, IATA
 - · Class Void
- · Packing group
- · DOT, ADR, IMDG, IATA Void
- Environmental hazards: Not applicable.
- · Special precautions for user Not applicable.
- · UN "Model Regulation": Void

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
 - · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65
 - · Chemicals known to cause cancer:

91-20-3 naphthalene

- Carcinogenic categories
- EPA (Environmental Protection Agency)

91-20-3 naphthalene

C, CBD

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- Clean Water Act
- Clean Water Act Toxic Pollutants (40 CFR 401.15)

None of the ingredients is listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms GHS08
- Signal word Danger

(Contd. on page 7)

Printing date 06/18/2019 Reviewed on 06/18/2019

Product name: 53609: Engine Coolant

(Contd. from page 6)

Hazard-determining components of labeling:

Distillates (petroleum), hydrotreated light naphthenic

Solvent naphtha (petroleum), heavy arom.

Hazard statements

H304 May be fatal if swallowed and enters airways. H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P301+P310 If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting. P331

P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

National regulations:

Information about limitation of use:

Note for Canada -- this material contains ~10% of an NDSL listed substance.

Other regulations, limitations and prohibitive regulations

This product contains acute and/or chronic hazards under SARA 311 or 312.

- Other classification information
- NFPA ratings (scale 0 4)



Health = 1 Fire = 1 Reactivity = 0

HMIS-ratings (scale 0 - 4)



1 Health = 1 1 Fire = 1 REACTIVITY Reactivity = 0

16 Other information

The information in this Safety Data Sheet relates only to the specific material designated herein. It does not relate to use in combination with any other material or in any process. This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of the manufacturer/supplier. The data on this sheet are related only to the specific material designated herein, and the information available for all ingredients at the time of creation. Manufacturer/supplier assumes no responsibility for use or reliance upon these data. Any information that is withheld herein (such as exact chemical identity or exact concentration) has been reserved as a trade secret as per applicable regulations.

- Contact: ABH
- Date of preparation / last revision 06/18/2019 / -
- Abbreviations and acronyms:

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3