

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : 53660 Master Leak Shield HVAC – 1.5 to 6 Tons
 Product code : 53660

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Master Leak Shield HVAC Plus UV Dye is used to seal small leaks in refrigeration systems and help detect leaks.

1.3. Supplier

Mastercool, Inc.
 1 Aspen Drive
 Randolph, NJ 07869 - USA
 T 973-252-9119 - F 973-252-2455

1.4. Emergency telephone number

Emergency number : USA PHONE:1-800-373-7542, INT'L: 1-484-951-2432

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Reproductive toxicity Category 2	H361 Suspected of damaging fertility or the unborn child
Specific target organ toxicity (repeated exposure) Category 2	H373 May cause damage to organs through prolonged or repeated exposure
Hazardous to the aquatic environment - Chronic Hazard Category 2	H411 Toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

H280 - Contains gas under pressure; may explode if heated
 H361 - Suspected of damaging fertility or the unborn child
 H373 - May cause damage to organs through prolonged or repeated exposure
 H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P251 - Pressurized container: Do not pierce or burn, even after use.
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P308+P313 - If exposed or concerned: Get medical advice/attention.
 P314 - Get medical advice/attention if you feel unwell.
 P391 - Collect spillage.
 P405 - Store locked up.
 P412 - Do not expose to temperatures exceeding 50 °C/ 122 °F.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

Other hazards not contributing to the classification : Contains gas under pressure; may burst if heated.

2.4. Unknown acute toxicity (GHS US)

Not applicable

53660 MASTER LEAK SHIELD HVAC – 1.5 to 6 Tons

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
phenyl isopropyl phosphate	(CAS-No.) 68937-41-7	0.01 - 1	Repr. 2, H361 STOT RE 2, H373 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

- Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
- Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

No additional information available

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

53660 MASTER LEAK SHIELD HVAC – 1.5 to 6 Tons

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : CAUTION: COMPRESSED GAS. Do not puncture, incinerate or store above 120°F. Do not store in passenger compartment of automobile. Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Avoid contact with skin and eyes. . Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Do not store above 120°F. Keep container closed when not in use.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight.
Storage temperature : < 49 °C Do not store in passenger compartment of automobiles.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

phenyl isopropyl phosphate (68937-41-7)

Not applicable

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

The use of gloves impervious to the specific material handled is advised to prevent skin contact. Suggested protective material: Nitrile, 4.5 mil thickness, tested at 3.5 ml and above with no breakthrough time after 240 minutes. Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

Normally not required. Where there is potential for airborne exposure above the exposure limit an approved air purifying respirator equipped with Type R or P95 particle filters may be used. Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid.
Appearance : Clear.
Color : Green-yellow.
Odor : Characteristic.
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : Non flammable.
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available

53660 MASTER LEAK SHIELD HVAC – 1.5 to 6 Tons

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon Dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified (Not expected to cause cancer. This oil meets the IP-346 criteria of less than 3 percent PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.)
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: May cause damage to organs through prolonged or repeated exposure.

phenyl isopropyl phosphate (68937-41-7)

Specific target organ toxicity – repeated exposure	May cause damage to organs through prolonged or repeated exposure.
--	--

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.

53660 MASTER LEAK SHIELD HVAC – 1.5 to 6 Tons

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life.

12.2. Persistence and degradability

28337 HVAC Leak Stop BOV + UV Dye	
Persistence and degradability	Not established.
phenyl isopropyl phosphate (68937-41-7)	
Persistence and degradability	Biodegradability in water: no data available.

12.3. Bioaccumulative potential

28337 HVAC Leak Stop BOV + UV Dye	
Bioaccumulative potential	Not established.
phenyl isopropyl phosphate (68937-41-7)	
Log Pow	4.9 - 5.2
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Proper Shipping Name (DOT) : Aerosols
LTD QTY
Class (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115
Hazard labels (DOT) : Limited Quantity



Dangerous for the environment : Yes
Marine pollutant : Yes



Other information : No supplementary information available.

53660 MASTER LEAK SHIELD HVAC – 1.5 to 6 Tons

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transportation of Dangerous Goods

Transport by sea

Marine pollutant : Yes



Air transport

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

28337 HVAC Leak Stop BOV + UV Dye

All components of this product are listed or are not regulated U.S. Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

15.3. US State regulations

28337 HVAC Leak Stop BOV + UV Dye

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
U.S. - California - Proposition 65 - Other information	Warning this product can expose you to Diisodecyl phthalate which is known to the State of California to cause birth defects or other reproductive harm. For more information www.P65Warnings.ca.gov .

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 03/05/2019
Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Other information : None.

53660 MASTER LEAK SHIELD HVAC – 1.5 to 6 Tons


Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases: see section 16:

H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

- NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.
- NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



SDS US (GHS HazCom 2012)

This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of Mastercool, Inc. The data on this sheet related only to the specific material designed herein. Mastercool, Inc. assumes no legal responsibility for the use or reliance upon these data.