

91050-290 / R290 Refrigerant

Section 1. Identification

GHS product identifier: Propane

Product Use: Refrigerant

Company: Mastercool Inc.
1 Aspen Drive
Randolph, NJ 07869

For more information call: 973-252-9119
(Mon-Fri, 9:00am-5:00pm)

In case of emergency call: **ChemTel (800) 255-3924 (24/7)**

Section 2. Hazards Identification

OSHA/HSC status: This material is considered hazardous by the OSHA Hazard Communication Standard. (29 CFR 1910.1200).

Classification of the Substance of mixture: FLAMMABLE GASES – Category 1
GASES UNDER PRESSURE – Liquified gas

GHS label elements

Hazard pictograms:



Signal word: Danger

Hazard statements: Extremely flammable gas.
Contains gas under pressure; may explode if heated.
May form explosive mixtures in Air.
May cause frostbite.
May displace oxygen and cause rapid suffocation.

Precautionary statements

General: Read and follow all Safety Data Sheets (SDS'S) before use. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Close valve after each use and when empty. Use equipment rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. Use a back flow preventative device in the piping. Use only equipment of compatible materials of construction. Always keep container in upright position. Approach suspected leak area with caution.

Prevention: Use and store only outdoors or in a well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

R290

Section 2. Hazards Identification (*continue*)

| | |
|---------------------------------|---|
| Storage: | Protect from sunlight when ambient temperature exceeds 52°C/125°F. Store in a well-ventilated place. |
| Response: | Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. |
| Disposal: | Not applicable |
| Hazard not otherwise classified | Liquid can cause burns like frostbite. In addition to any other important health or physical hazards, this product may displace oxygen and cause rapid suffocation. |

Section 3. Composition/information on ingredients

| | |
|-------------------------------------|---|
| Substance/mixture: | Substance |
| Chemical name: | Propane |
| Other mean of identification: | Propyl hydride; n-Propane; Dimethyl methane; Bottled gas; propane in gaseous state; propane liquefied, n-Propane; Dimethylmethane; Freon 290; Liquefied petroleum gas; Lpg; Propyl hydride; R 290; C3H8; UN 1075; UN 1978; A-108; Hydrocarbon propellant. |
| <u>CAS number/other identifiers</u> | |
| CAS number: | 74-98-6 |
| Product Code: | TBA |

| Component name | % | CAS number |
|----------------|-----|------------|
| Propane | 100 | 74-98-6 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4. First aid measures

Description of necessary first aid measures

| | |
|--------------|--|
| Eye contact: | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs. |
| Inhalation: | Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |



Section 4. First aid measures (continue)

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. In case of contact with liquid, warm frozen tissues slowly with lukewarm water and get medical attention. Do not rub affected area. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if adverse health effects persist or are severe. Ingestion of liquid can cause burns like frostbite. If frostbite occurs, get medical attention. Never give anything by mouth to an unconscious person. If

unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. As this product rapidly becomes a gas when released, refer to the inhalation section.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Liquid cause burns like frostbite.
 Inhalation : No known significant effects or critical hazards.
 Skin contact : Dermal contact with rapidly evaporating liquid could result in freezing of the tissue or frostbite.
 Frostbite : Try to warm up the frozen tissues and seek medical attention.
 Ingestion : Ingestion of liquid can cause burns like frostbite.

Over-exposure sign/symptoms

Eye contact : Adverse symptoms may frostbite
 Inhalation : No data recorded
 Skin contact : Adverse symptoms may frostbite
 Ingestion : Adverse symptoms may frostbite

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
 Specific treatments : No specific treatments
 Protection on first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 5. Fire-Fighting measures

Extinguishing media

Suitable Extinguishing media : Use an extinguishing agent suitable for the surrounding fire.
 Unsuitable Extinguishing media : None Known.

Specific hazards arising from the chemical : Contains gas under pressure. Extremely flammable gas. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Gas may accumulate in low or confined



Section 5. Fire-Fighting measures (continue)

Hazardous thermal:
Decomposition products

areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion.

: Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions
for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. If involved in fire, shut off flow immediately if it can be done without risk.

Special protective
equipment for fire-fighters

If this is impossible, withdraw from area and allow fire to burn. Fight fire from protected location or maximum possible distance. Eliminate all ignition sources if safe to do so.

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. For incidents involving large quantities, thermally insulated undergarments and thick textile or leather gloves should be worn.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions: Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).



Section 6. Accidental release measures (continue)

Methods and materials for containment and cleaning up

Small spill: Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment.

Large spill: Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures: Put on appropriate personal protective equipment (see Section 8). Contains gas under pressure. Do not get in eyes or on skin or clothing. Avoid breathing gas. Empty containers retain product residue and can be hazardous. Do not puncture or incinerate container. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.

Advice on general Occupational hygiene: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage Including any incompatibilities: Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed and sealed until ready for use. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F).

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Propane **NIOSH REL (United States, 10/2013).**
TWA: 1800 mg/m³ 10 hours.
TWA: 1000 ppm 10 hours.
OSHA PEL (United States, 2/2013).
TWA: 1800 mg/m³ 8 hours.
TWA: 1000 ppm 8 hours.

Section 8. Exposure controls/personal protection (continue)

OSHA PEL 1989 (United States, 3/1989).

TWA: 1800 mg/m³ 8 hours.

TWA: 1000 ppm 8 hours.

Appropriate engineering
Controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure
Controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. If contact with the liquid is possible, insulated gloves suitable for low temperatures should be worn. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.



Section 8. Exposure controls/personal protection (continue)

Other skin protection :Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection :Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Gas. [Liquefied gas]
 Color : Colorless.
 Molecular weight : 44.11 g/mole
 Molecular formula : C3-H8
 Boiling/condensation point : -161.48 °C (-258.7 °F)
 Melting/freezing point : -187.6°C (-305.7°F)
 Critical temperature : 96.55°C (205.8°F)
 Odor : Odorless.
 Odor threshold : Not available.
 pH : Not available.
 Flash point : Closed cup: -104°C (-155.2°F).
 Burning time : Not applicable.
 Burning rate : Not applicable.
 Evaporation rate : Not available.
 Flammability(solid, gas) : Extremely flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and oxidizing materials.

Lower and upper explosive (flammable) limits : Lower: 1.8%
 Upper: 8.4%

Vapor pressure : 109 (psig)
 Vapor density : 1.6 (Air = 1)
 Gas Density (lb/ft³) : 0.116 (25°C / 77 to °F)
 Relative density : Not applicable.
 Solubility : Not available.
 Solubility in water : 0.0244 g/l
 Partition coefficient n-octano/water : 1.09
 Auto-ignition temperature :
 Flash point : 287°C (548.6°F)
 Decomposition temperature : Not available.
 SADT : Not available.
 Viscosity : Not applicable.



Section 10. Stability and reactivity

| | |
|------------------------------------|---|
| Reactivity | : No specific test data related to reactivity available for this product. |
| Chemical stability | : The product is stable. |
| Possibility of hazardous Reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). Do not ressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow gas to accumulate in low or confined areas. |
| Incompatible materials | : Oxidizers |
| Hazardous decomposition | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |
| Hazardous polymerization | : polymerization will not occur. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| | |
|--|------------------|
| Irritation and Corrosion | : Not Available. |
| Sensitization | : Not Available. |
| Mutagenicity | : Not Available. |
| Carcinogenicity | : Not Available. |
| Reproductive toxicity | : Not Available. |
| Teratogenicity | : Not Available. |
| Specific target toxicity (single exposure) | : Not Available. |
| Specific target toxicity (repeated exposure) | : Not Available. |
| Aspiration hazard | : Not Available. |

Potential acute health effects

| | |
|--------------|--|
| Eye contact | : Liquid can cause burns like frostbite. |
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : Dermal contact with rapidly evaporating liquid could result in freezing of the tissues or frostbite. |
| Ingestion | : Ingestion of liquid can cause burns like frostbite. |

Symptoms related to the physical, chemical and toxicological characteristics

| | |
|--------------|---|
| Eye contact | : Adverse symptoms may include frostbite |
| Inhalation | : No specific data. |
| Skin contact | : Adverse symptoms may include frostbite. |
| Ingestion | : Adverse symptoms may include frostbite |



Section 11. Toxicological information (continue)

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic effects

General : No known significant effects or critical hazards.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.
Developmental : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates : Not available.

Section 12. Ecological information

Toxicity : Not available.
Persistence and degradability : Not available.

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| Propane | 1.09 | - | Low |

Soil/water partition coefficient (K_{oc}) : Not available.
Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.








R290

Section 11. Toxicological information (continue)

Empty Airgas-owned pressure vessels should be returned to Airgas. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transportation information

| | DOT | TDG | Mexico | IMDG | IATA |
|-------------------------|--|--|---|---|--|
| UN# | UN1978 | UN1978 | UN1978 | UN1978 | UN1978 |
| UN proper shipping name | PROPANE | PROPANE | PROPANE | PROPANE | PROPANE |
| Transport hazard class | 2.1  | 2.1  | 2.1  | 2.1  | 2.1  |
| Packaging group | n/a | n/a | n/a | n/a | n/a |
| Environment | No. | No. | No. | No. | No. |
| Additional information | Limited quantity Yes. Packaging instruction Passenger aircraft Quantity limitation: Forbidden. Cargo aircraft Quantity limitation: 150 kg Special provisions 19, T50 | Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2). Explosive Limit and Limited Quantity Index 0.125 ERAP Index 3000 Passenger Carrying Ship Index 65 Passenger Carrying Road or Rail Index Forbidden Special provisions 29, 42 | n/a | n/a | Passenger and Cargo Aircraft Quantity limitation: 0 Forbidden Cargo Aircraft Only Quantity limitation: 150 kg |

"Refer to CFR 49 (or authority having jurisdiction) to determine the information required for shipment of the product."

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.



Section 15. Regulatory information

U.S Federal regulations : **TSCA 8(a) CDR Exempt/Partial exemption:** Not determined
United States inventory (TSCA 8b): All components are listed or exempted.
Clean Air Act (CAA) 112 regulated flammable substances: propane

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Not listed.

Clean Air Act Section 602 Class I Substances : Not listed.

Clean Air Act Section 602 Class II Substances : Not listed.

DEA List I Chemicals (Precursor Chemicals) : Not listed.

DEA List II Chemicals (Essential Chemicals) : Not listed.

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Fire hazard.Sudden release of pressure.

Composition/information on ingredients

| Name | % | Fire hazard | Sudden release of pressure | Reactive | Immediate (acute) health hazard | Delayed (chronic) health hazard |
|---------|-----|-------------|----------------------------|----------|---------------------------------|---------------------------------|
| Propane | 100 | Yes. | Yes. | No. | No. | No. |

State regulations

Massachusetts : Listed.
 New York : None of the components are listed.
 New Jersey : Listed.
 Pennsylvania : Listed.
 International regulations : n/a.



Section 16. Other information

Canada Label Requirements : Class A: Compressed Gas.
Class B-1: Flammable Gas.

Hazardous Material Information System (U.S.A.)

| | |
|------------------|---|
| Health | 1 |
| Flammability | 4 |
| Physical hazards | 2 |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety. Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

| Classification | Justification |
|---------------------------|-----------------|
| Flam. Gas 1, H220 | Expert judgment |
| Press. Gas Liq. Gas, H280 | Expert judgment |

History

Date of printing : 11/25/2016
Date of issue/ revision : 11/25/2016
Previous issue : n/a
Version : 0.01



Section 16. Other information (continue)

Key to abbreviation

: ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations