




ISOBUTANE MANIFOLDS WITH THERMOPLASTIC SERVICE HOSES



93618-TP

ALUMINUM R1270, R290, R600A 2-WAY MANIFOLD GAUGE SETS

- Large 80 mm gauges (Bar/PSI/°C) with easy to read temperatures scales
- Includes 2 mm thermoplastic service hoses with 1/4" SAE female swivel fittings for maximum precision on small capacity systems

93618-RB-TP	Aluminum 2-way manifold gauge set with (3) 45 cm (18") thermoplastic service hoses packaged in a cardboard box
93624-RB-TP	Aluminum 2-way manifold gauge set with (3) 60 cm (24") thermoplastic service hoses packaged in a cardboard box
93103-RB	Aluminum 2-way manifold with 80 mm gauges only
RBL	R1270, R290, R600a (Bar/PSI/°C) low side (80 mm) replacement gauge
RBH	R1270, R290, R600a (Bar/PSI/°C) high side (80 mm) replacement gauge



THERMOPLASTIC SERVICE HOSE ASSEMBLIES - 1/4" SAE FEMALE SWIVEL FITTINGS

- EN 1736 and ISO 13971 - Class 2
- Inner Diameter 2 mm
- Outer Diameter 5.9 mm
- Tolerances 0.1 mm
- Bending Radius 10 mm
- Max Allowable Pressure 60 bar (870 psi)
- Working Temperature 120°C
- Min/Max Allowable Temperature -40 to 130°C
- Weight 25 g/m

44180-TPC	Set of 3-18" (45 cm) thermoplastic service hoses with 1/4" SAE female swivel fittings
44240-TPC	Set of 3-24" (60 cm) thermoplastic service hoses with 1/4" SAE female swivel fittings
44181-TPC	18" (45 cm) thermoplastic service hose with 1/4" SAE female swivel fittings
44241-TPC	24" (60 cm) thermoplastic service hose with 1/4" SAE female swivel fittings

* All gauges above are available with shock resistant gauge protectors – to order, add -G after the Part#